

Range	Load capacity	Hook path	Hoist speed m/min			Group of mechanism ** FEM/ISO	Load capacity	Hook path	Hoist speed m/min		
	t		m	1	2		3		t	m	1
DR 3	2/1						4/1				
	1.6	12 20	12/2	18/3	1-25 *	2m / M5	3.2	6 10	6/1	9/1.5	0.5-12.5 *
	1.25					3m / M6	2.5				
	1		4m / M7	2							
DR 5	2/1						4/1				
	3.2	12 20 30	9/1.5	12/2	0.8-16 *	1Am / M4	6.3	6 10 15	4.5/0.8	6/1	0.4-8 *
	2.5		12/2	18/3	1-25 *	2m / M5	5		6/1	9/1.5	0.5-12.5 *
	2					3m / M6	4				
	1.6		4m / M7	3.2							
							4/2				
						1Am / M4	3.2	9.9 16.3	9/1.5	12/2	0.8-16 *
						2m / M5	2.5		12/2	18/3	1-25 *
						3m / M6	2				
						4m / M7	1.6				
DR 10	2/1						4/1				
	6.3	12 20 30 40	8/1.4	0.4-9 *	1-18 *	1Am / M4	12.5	6 10 15 20	4/0.7	0.2-4.5*	0.5-9 *
	5		10/1.7	1-18 *	1-25 *	2m / M5	10		5/0.8	0.5-9 *	0.5-12.5 *
	4					3m / M6	8				
	3.2		4m / M7	6.3							
							4/2				
						1Am / M4	6.3	5.8 11.35 18.4 25.2	8/1.4	0.4-9 *	1-18 *
						2m / M5	5		10/1.7	1-18 *	1-25 *
					3m / M6	4					
					4m / M7	3.2					

* Loads weighing up to one third of the rated load are moved at 1.5 times the rated speed (Prohub)

** Gearbox service life 20 % longer than the ISO / FEM full load service life